



Wyzwalacz wzrostowy, 110-415V, 1JC

Typ **ZP-ASA/230**
 Catalog No. **248439**

Program dostaw

Funkcja podstawowa			Akcesoria do wyłącznika ochronnego Akcesoria do zespolonego wyłącznika różnicowoprądowego FI/LS
Funkcja podstawowa – akcesoria			Wyzwalacz wzrostowy
Aplikacja			Aparaty łączeniowe do zastosowań w przemyśle i budynkach funkcjonalnych
Asortyment			Akcesoria
Side mounting			for fitting on left to: FAZ, FRBmM-1N, Z-MS
Diagram łączenia			

Świadectwo typu zgodnie z IEC/EN 61439

Dane techniczne dla zaświadczenia rodzaju konstrukcji			
Robocza temperatura otoczenia min.	°C		-5
Robocza temperatura otoczenia maks.	°C		40

Dane techniczne zgodne z ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Other
Additional equipment			Shunt release (for power circuit breaker)
Attached at delivery			No
Assembly width (TE)			1
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	0
Nominal rated voltage		V	230
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	2.1

Wymiary

